

1/2" SPRINKLERS



AQ-5LA7 / AQ-5LA15

- Available in 1/2" BSP/NPT Male Thread Connection
- Bronze Body & Arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Springs and Pivot Pin
- AQ-5LA7 - Low Trajectory Angle 7°
- AQ-5LA15 - Low Trajectory Angle 15°



AQ-5WLA7 / AQ-5WN23

- Available in 1/2" BSP/NPT Male Thread Connection
- Wedge Drive Sprinkler
- Bronze Body & Arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Springs and Pivot Pin
- AQ-5WLA7 - Low Trajectory Angle 7°
- AQ-5WN23 - Low Trajectory Angle 23°



AQ-05PC 270.1300051

- Available in 1/2" BSP/NPT Male Thread Connection
- Bronze Body & Zamac pressure die casted arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Trip Mechanism
- Both Part Circle & Full Circle operations possible
- Part Circle Operation ranging from 20° to 340°
- Trajectory Angle 25°
- For agricultural use, bronze arm sprinkler also available



AQ-22 250.1513700

- Available in 1/2" Male Thread Connection
- Color coded nozzles for easy identification of size
- Body, Arm, Bearing & Nozzles made of Delrin for durability
- Specially designed Bayonet nozzles
- Stainless Steel Springs & Pivot Pin
- Trajectory Angle 24°



AQ-22LA / 22LAW

- Available in 1/2" Male Thread Connection
- Color coded nozzles for easy identification of size
- Body, Arm, Bearing & Nozzles made of engineering plastic (Delrin) for durability
- Specially designed Bayonet Nozzles
- Stainless Steel Springs & Pivot Pin
- Trajectory Angle available in 9°, 12° & 14°
- For low pressure application, wedge drive sprinkler (120) also available



AQ-22PC 250.1513731

- Available in 1/2" Male Thread Connection
- Body Arm, Bearing & Nozzles made of engineering plastic (Delrin) for durability
- Specially designed Bayonet nozzles
- Stainless Steel Springs & Pivot Pin
- Both Part/Full Circle operations possible
- Part Circle Operation ranging from 15° to 345°
- Trajectory Angle 25°

3/4" SPRINKLERS



AQ-20CS

- Available in 3/4" BSP/NPT Male Thread Connection
- Bronze Body & Arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Springs & Pivot Pin
- Trajectory Angle 27°
- Available in low Trajectory Angle 10° also (For better coverage in wind conditions)



AQ-20AF 270.1300037

- Available in 3/4" BSP/NPT Male Thread connection
- Bronze Body & Arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Springs & Pivot Pin
- Cap made of LLDPE for durability
- Anti frost model
- Trajectory Angle 27°



AQ-20PC 270.1300031

- Available in 3/4" BSP/NPT Male Thread connection
- Bronze Body & Arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Springs & Pivot Pin
- Stainless Steel Trip Mechanism
- Both Part Circle & Full Circle operations possible
- Part Circle Operation ranging from 20° to 340°
- Trajectory Angle 25°



AQ-25

- Available in 3/4" BSP/NPT Male Thread Connection
- Bronze Body & Arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Springs & Pivot Pin
- Trajectory Angle 27°
- Available in low Trajectory Angle 10° also (For better coverage in wind conditions)



AQ-46 250.1512700

- Available in 3/4" BSP/NPT Male Thread connection
- Bronze Body & Arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Springs & Pivot Pin
- Cap made of LLDPE for durability
- Anti frost model
- Trajectory Angle 27°



AQ-46PC 250.1512730

- Available in 3/4" BSP/NPT Male Thread connection
- Bronze Body & Arm
- Brass Bearing Sleeve & Nipple
- Stainless Steel Springs & Pivot Pin
- Stainless Steel Trip Mechanism
- Both Part Circle & Full Circle operations possible
- Part Circle Operation ranging from 20° to 340°
- Trajectory Angle 25°

FLOWER SYSTEM

TAP TIMER

IP 68 CONTROLLERS

CONTROLLERS

SENSORS

ELECTRIC VALVES

FITTINGS

VALVE BOXES

SPRINKLERS

DRIP

COMPRESSION FITTINGS

ACCESSORIES

AGRICULTURE