# **BTT**

Take advantage of smartphone-controlled, above-ground irrigation for easier access to the hose tap.

## **KEY BENEFITS**

- · Number of zones:
  - 1 or 2 (fixed models)
- · Battery-operated tap timer with Bluetooth® control
- 1 smartphone manages an unlimited number of controllers
- 1-second to 24-hour run time with 4 start times
- Cycling mode repeats continuously within user-defined water windows, perfect for drip systems or germinating seeds
- Suspend irrigation up to 99 days during the off-season, perfect for seasonal markets
- Manual push-button operation for quick operation without a smartphone
- Automatic water shutoff after 1 hour prevents water waste
- Blinking LED low-battery alert indicates battery replacement
- Alkaline batteries included for quicker installation
- · Includes quick coupler adapter

#### **OPERATING SPECIFICATIONS**

- Two 1.5V AA alkaline batteries (included)
- Flow rate: 1.9 to 2,271 L/H
- Recommended pressure: 0.5 to 8 bar (50 to 800 kPa)
- · See friction loss chart
- Bluetooth 4.0/4.2 (BLE)
- Approvals: Plastic IPX6 (outdoor), UL, cUL, FCC, CE, RCM, ISED
- · Warranty period: 2 years

## **APP SPECIFICATIONS**

- iOS® 9.0 or above, Android™ 4.4 or above
- Maximum communication distance: 10 m
- See all app features at hunter.info/BTT

втт	
Model	Description
BTT-101	1-zone Bluetooth Tap Timer, 1" BSP and ¾" hose thread, quick coupler adapter
BTT-201	2-zone Bluetooth Tap Timer, 1" BSP and ¾" hose thread, quick coupler adapter

BTT ACCESSORIES		
Model	Description	
BTT-LOC	BTT adapter for 16-18 mm dripline	
PRLG203FH3MH	1.4 bar (140 kPa) pressure regulator, ¾" hose thread	
PRLG253FH3MH	1.7 bar (170 kPa) pressure regulator, ¾" hose thread	
PRLG303FH3MH	2 bar (200 kPa) pressure regulator, ¾" hose thread	
PRLG403FH3MH	2.8 bar (280 kPa) pressure regulator, ¾" hose thread	

The Bluetooth\* word mark and logos are registered trademarks owned by Bluetooth SIG Inc. and any use of such marks by Hunter Industries is under licence. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under licence. Android is a trademark of Google LLC.



BTT-101 Inlet diameter: ¾" and 1" Outlet diameter: ¾" Height: 16.8 cm Width: 12 cm Depth: 6 cm



BTT-LOC (optional) Inlet diameter: ¾" Outlet diameter: 16-18 mm dripline Height: 7 cm Width: 3 cm



BTT-201 Inlet diameter: ¾" and 1" Outlet diameter: ¾" Height: 15.7 cm Width: 13.5 cm Depth: 7.6 cm



Pressure Regulator (optional) Inlet diameter: ¾" Outlet diameter: ¾" Height: 7 cm Width: 4 cm

## BTT



To control drip irrigation applications with BTT, use the BTT-LOC Drip Adapter, which connects BTT to HDL surface and subsurface systems.

## Compatible with:



**HDL Dripline**